

# Securilath™ HD1

**DESCRIPTION:** Large, Expanded, Flattened, Steel

**TYPICAL APPLICATIONS: Security** 

**SKU Range Form** Pattern Securilath™ HD1 Securilath™ HD1 Flattened **Profile Longway Aperture Shortway Aperture** (LWA) (SWA) Diamond 42.93mm 14.22mm Strand Thickness AF\* Strand Width AF\* Material (SWDT) (STK) Steel 4.60mm 2.69mm **Finish** Open Area (%) Weight (KG/EA) Mill Finish 61% 25.60kg







LPS 1175: Issue 8 Cert No. 731n

**LPCB SR2.** LPS 1175: Issue 8. When installed per installation guide within certificate #731n

## \*AF: After Flattening

2440mm

Sheet (LWM)

If not otherwise specified, tolerances are in line with our standard factory tolerances available upon request. Due to the manufacturing processes and the nature of expanded metal, all dimensions are within nominal tolerances with no guarantee given in respect of squareness or flatness nor can we guarantee that expanded mesh will be free from surface marks, knife marks and scratches. 'LWP' and 'SWP' dimensions are measured between knuckle centres for raised mesh.

Sheet (SWM)

1220mm

#### **ACCREDITATIONS**

With our strong heritage and experience, we pride ourselves on delivering a quality product and working to the highest possible standard. Below is just a selection of the awarding bodies and accreditors who recognise our dediction to delivering an impeccable service and rigorously tested product.










# Securilath™ HD1

#### **MESH MEASURING GUIDE**

Our guide to measuring raised and flattened meshes, and mesh orientation.

#### **MESH STRUCTURE**

#### SHEET ORIENTATION



### **QUALITY INFORMATION**

Unless otherwise specifically stated all specifications and particulars of weights and dimensions stated are approximate only and are manufactured to nominal manufacturing tolerances.

In the spirit of continuous product development and improvement, we reserve the right to change product specifications without notice.

### **HEALTH & SAFETY INFORMATION**

#### **COSHH**

We are not aware of any risk to individuals arising from chemicals or other substances present on or in our products from reasonable usage. However, there exists the possibility of superficial injury in the form of cuts or grazes due to the nature of metal generally. Suitable PPE should be used when handling our product.